

## Performance table in accordance with EN IEC 63136

### (Krupps model)

	Advance			Uniko (*)						Link
Model	C432-BT	C537T-BT	CH110-BT	EL42E	EL51E	EL60E	EL60TH	EL70E		
Model		C537T-BTS	CH110-BTS		ELS51E	ELS60E	ELS60TH			
Energy consumption for initial fill (Es)	1.026	1.391	1.930	1.026	1.391	1.930	1.930	2.029	kWh	
Water consumption for initial fill (Vs)	13.3	19.7	32	13.3	19.7	32	32	32	l	
Start-up time (Ts)	1670	1980	1750	1670	1980	1750	1750	1840	s	
Number of plates per rack	10	18	18	10	18	18	18	22		
Cleaning performance (Xc)	81	98	96.9	81	98	96.9	96.9	95.3	%	
Resoiling performance (Xr)	2	14	1	2	14	1	1	2		
Energy consumption per cycle (Ec)	0.236	0.316	0.333	0.236	0.316	0.333	0.333	0.462	kWh	
Water consumption per cycle (Vc)	2.8	3.3	2.3	2.8	3.3	2.3	2.3	2.3	l	
Energy consumption per plate (Ep)	0.026	0.020	0.021	0.026	0.020	0.021	0.021	0.021	kWh	
Water consumption per plate (Vp)	0.31	0.21	0.15	0.31	0.21	0.15	0.15	0.11	l	
Average programme time (Tpr)	117	117	117	117	117	117	117	117	s	
Average cycle time (Tc)	426	284	260	426	284	260	260	286	s	
Power ready-to-use mode (Pu)	0.200	0.308	0.377	0.134	0.182	0.203	0.203	0.223	kW	

(\*) Energy saving mode activated

No drain pump on board

## Performance table in accordance with EN IEC 63136

### (Krupps model)

	Advance											
Model	C327	C426	C432	C537	C537T (D.W.)	C537T	C640 (D.W.)	C640	CH100	CH110	CH150	
Model			C432-S									
Energy consumption for initial fill (Es)	0.601	0.756	0.795	1.420	1.446	1.424	1.589	1.540	1.397	2.206	1.982	kWh
Water consumption for initial fill (Vs)	11	12.75	14.75	18.5	20.5	20.5	23.75	23.5	18.5	31.7	31.5	l
Start-up time (Ts)	1000	1120	1240	2205	1805	1740	2010	1955	1620	1734	1545	s
Number of plates per rack	6	10	10	18	18	18	22	22	18	18	22	
Cleaning performance (Xc)	87	81	81	98	98	98	97	97	96.9	96.9	95.3	%
Resoiling performance (Xr)	5	2	2	14	14	14	10	10	1	1	2	
Energy consumption per cycle (Ec)	0.178	0.187	0.203	0.274	0.258	0.264	0.274	0.279	0.312	0.323	0.357	kWh
Water consumption per cycle (Vc)	2	2.25	2.25	2.5	2.5	2.5	2.25	2.5	2.5	2.25	2.5	l
Energy consumption per plate (Ep)	0.030	0.019	0.020	0.015	0.014	0.015	0.012	0.013	0.017	0.018	0.016	kWh
Water consumption per plate (Vp)	0.33	0.23	0.23	0.14	0.14	0.14	0.10	0.11	0.14	0.13	0.11	l
Average programme time (Tpr)	120	120	120	120	120	120	120	120	120	120	120	s
Average cycle time (Tc)	310	347	350	430	235	248	321	319	321	247	265	s
Power ready-to-use mode (Pu)	0.176	0.180	0.183	0.272	0.207	0.266	0.234	0.305	0.393	0.429	0.363	kW

No drain pump on board