

Performance table in accordance with EN IEC 63136

(Krupps model)

| | Advance | | | Uniko (*) | | | | | | Link |
|--|---------|-----------|-----------|-----------|--------|--------|---------|-------|-----|------|
| Model | C432-BT | C537T-BT | CH110-BT | EL42E | EL51E | EL60E | EL60TH | EL70E | | |
| Model | | C537T-BTS | CH110-BTS | | ELS51E | ELS60E | ELS60TH | | | |
| Energy consumption for initial fill (Es) | 1.026 | 1.391 | 1.930 | 1.026 | 1.391 | 1.930 | 1.930 | 2.029 | kWh | |
| Water consumption for initial fill (Vs) | 13.3 | 19.7 | 32 | 13.3 | 19.7 | 32 | 32 | 32 | l | |
| Start-up time (Ts) | 1670 | 1980 | 1750 | 1670 | 1980 | 1750 | 1750 | 1840 | s | |
| | | | | | | | | | | |
| Number of plates per rack | 10 | 18 | 18 | 10 | 18 | 18 | 18 | 22 | | |
| Cleaning performance (Xc) | 81 | 98 | 96.9 | 81 | 98 | 96.9 | 96.9 | 95.3 | % | |
| Resoiling performance (Xr) | 2 | 14 | 1 | 2 | 14 | 1 | 1 | 2 | | |
| Energy consumption per cycle (Ec) | 0.236 | 0.316 | 0.333 | 0.236 | 0.316 | 0.333 | 0.333 | 0.462 | kWh | |
| Water consumption per cycle (Vc) | 2.8 | 3.3 | 2.3 | 2.8 | 3.3 | 2.3 | 2.3 | 2.3 | l | |
| Energy consumption per plate (Ep) | 0.026 | 0.020 | 0.021 | 0.026 | 0.020 | 0.021 | 0.021 | 0.021 | kWh | |
| Water consumption per plate (Vp) | 0.31 | 0.21 | 0.15 | 0.31 | 0.21 | 0.15 | 0.15 | 0.11 | l | |
| Average programme time (Tpr) | 117 | 117 | 117 | 117 | 117 | 117 | 117 | 117 | s | |
| Average cycle time (Tc) | 426 | 284 | 260 | 426 | 284 | 260 | 260 | 286 | s | |
| | | | | | | | | | | |
| Power ready-to-use mode (Pu) | 0.200 | 0.308 | 0.377 | 0.134 | 0.182 | 0.203 | 0.203 | 0.223 | KW | |

(*) Energy saving mode activated

No drain pump on board