



ADVANCE RANGE C537-S

TYPE	Undercounter warewasher
LINE	ADVANCE RANGE
BASKET	500x500
SIZE	585x600x815h

ADVANCE line models with **automatic softener** breaks down limescale extremely effectively. The softener is completely **autonomous** and automatically adjusts its regeneration intervals according to the hardness of the inlet water; you only have to fill the salt tank whenever the 'no salt' message appears on the display. Regeneration of the resins takes place during washing cycles, so no downtime is required.

With the **C537-S** dishwasher, it is possible to wash glasses of different shapes and sizes as well as **18 plates per cycle** with Ømax 395mm thanks to the baskets provided, with a maximum output of 40 baskets/hour (720 plates/hour). The optional **drain pump** allows you to manage the drainage automatically and to perform a partial clean water change at each wash cycle.

The **ADVANCE** panel is the real strength of the line thanks to its **4 washing cycles** and one automatic drain cycle (with drain pump installed). On the control panel you can easily view the tank and boiler temperature, the messages of the **Self-diagnosis** system, the **Scheduled Maintenance** warning and the **intelligent Start button**, which changes colour to always display the dishwasher status very easily. The simple and extremely efficient electronic card offers the possibility of setting and controlling the rinsing and draining times, the washing and rinsing temperatures and the relative Thermostops, crucial for ensuring excellent washing results.

The bodywork is made entirely of **AISI 304 steel** and has been designed with all of the components in the front for **easy technical assistance**. Sturdy and reliable dishwashers to best deal with every moment of your day.

DISHWASHERS FEATURES	ADVANCE RANGE C537-S
Dimensions - (mm) L - P - H	585x600x815h
n° baskets/hour - (+55°C)	Max 40
Height glass max	365mm
Ø height plate max	395mm
Trays	GN 1/1 (Special basket required)
Tank heating element - Tank capacity	2,6kW - 24lt
Boiler heating element - Boiler capacity	2,5kW - 7,3lt
Washing pump	0,52kW / 0,7Hp
Total power input / Current	3,12kW / 16A
Standard input voltage	230V 50Hz
Recommended inlet water temperature	+55°C
Water hardness	>15 °f
Water consumption per cycle (inlet suggested pressure 2 BAR)	2,0lt
Adjustable detergent and rinse-aid dispenser	ELECTRIC
Built-in water softener	si
STANDARD EQUIPMENT	
Cutlery insert	2
Basket for glasses dim.500x500x100mm	1
Basket for 18 dishes dim.500x500x100mm	1
Salt funnel	1
OPTIONAL	
UNIKO touch display with IKLOUD Wi-Fi control	-
Booster pump kit 0,5Hp	●
Drain pump kit 32W with Ecoclean	●
Double wall for thermal and acoustic insulation +18mm	●
Stainless steel tank filter	●
Basket for trays with 4 compartments dim.500x500x200mm	●
Inclined basket for wine glasses dim.500x500x170mm	●
Kit 4 Stainless steel feet 50-70mm	●
"SOFT Door" Opening/Closing System	●
Start Cycle "SOFT Start"	●
"DOUBLE Load" double basket support	●

● Optional Installabile, - Optional not installabile

C537-S

