







ELITECH RANGE EL51E

TYPE	Undercounter warewasher
LINE	ELITECH RANGE
BASKET	500x500
SIZE	585x600x815h













With the EL51E dishwasher you can wash glasses of different shapes and sizes and 18 dishes per cycle with max Ø of 395mm thanks to the baskets provided, with a maximum productivity of 40 baskets/hour (720 dishes/hour). The drain pump optional allows you to handle draining automatically and perform a partial replacement of clean water at each wash. The addition of the Reverse Osmosis System, suitable detergents and tilted basket is the right answer for all establishments where perfect glasses and automatic drying are indispensable elements.

The dishwashers of the ELITECH line ensure maximum performance thanks to the standard Acquatech System which, through an atmospheric boiler and rinse pump, maintains constant temperature and pressure and optimum water consumption. Elitech ensures a sanitising rinse cycle and proves to be the perfect choice for canteens, nursing homes, pastry shops, bakers and butchers where compliance with HACCP rules is essential. For anyone seeking perfectly sparkling glasses, it is possible to connect a Reverse Osmosis System which purifies water and reduces detergent and rinse-aid consumption, ensuring excellent results and perfect glasses without the need for hand drying. The innovative UNIKO tempered glass touch screen display makes any operation simple and intuitive, from the choice of the most suitable wash cycle to its progress control, as well as constantly monitor the status of the dishwasher with ease. The large variety of wash cycles makes the dishwasher customisable according to your needs. Constant self-diagnosis allows you to minimise machine downtime, promptly warning the technician through the Wi-Fi IKLOUD control system that offers the possibility of remotely changing the dishwasher parameters and resolving the situation in real-time.

The electronic control allows you to manage various parameters to give you an absolute customisation level and the continuous self-diagnosis allows you to minimise machine downtime, suggesting some operations that need to be verified. The self-cleaning cycle at the end of the day cleans the wash tank and empties the hot water from the boiler, preventing limestone from building up inside. The standard double peristaltic electric rinse-aid and detergent dispenser ensures the best result from each wash cycle with great savings thanks to the precise dosage managed by the electronic card; whereas, the moulded washing and rinsing arms ensure great reliability and durability. The Thermo-stop function checks that washing and rinsing begin only when the desired temperature is reached. The bodywork is made entirely of AISI 304 steel and has been designed with all of the components in the front for easy technical assistance.

EN IEC 63136 COMPLIANT MODEL View the performance table

FRE C€ €












DISHWASHERS FEATURES	ELITECH RANGE EL51E
Dimensions - (mm) L - P - H	585x600x815h
n° baskets/hour - (+55°C)	Max 40
Height glass max	365mm
Ø height plate max	395mm
Trays	GN 1/1 (Special basket required)
Tank heating element - Tank capacity	2,6kW - 22lt
Boiler heating element - Boiler capacity	5,4kW - 7,3lt
Washing pump	0,52kW / 0,7Hp
Total power input / Current	5,92kW / 16A
Standard input voltage	430V3N - 50Hz
Recommended inlet water temperature	+55°C
Water hardness	7°f - 10°f
Water consumption per cycle (inlet suggested pressure 2 BAR)	2,4
Adjustable detergent and rinse-aid dispenser	STANDARD
Acquatech system rinse	STANDARD
STANDARD EQUIPMENT	
Cutlery insert	2
Basket for glasses dim.500x500x100mm	1
Basket for 18 dishes dim.500x500x100mm	1
OPTIONAL	
UNIKO touch display with IKLOUD Wi-Fi control	
Optional 230V/3+T	•
Drain pump kit 32W with Ecoclean	•
Boiler heating element 9kW	•
Double wall for thermal and acoustic insulation +18mm	•
Stainless steel tank filter	•
Reverse osmosis system	•
Basket for trays with 4 compartments dim.500x500x200mm	•
Inclined basket for wine glasses dim.500x500x170mm	•
Kit 4 Stainless steel feet 50-70mm	•
"SOFT Door" Opening/Closing System	•
Start Cycle "SOFT Start"	•
"DOUBLE Load" double basket support	•
•	
Optional Installabile, Optional not installable	

EL51E





APPROVED PRODUCT

