







ELITECH RANGE **EL991E**

TYPE	Warewasher
LINE	ELITECH RANGE
BASKET	2 x 600x670
SIZE	1440X860X2020/2300h

The EL991E warewasher is the answer for anyone who has to effectively wash objects measuring up to 575x645x825(h)mm inside its two baskets, thanks to the two wash pumps and two rinse pumps. It is suitable for washing baking trays, pots of various kinds, mixing bowls, utensils and even 52 dishes at each cycle as it is equipped with two baskets with a maximum productivity of 60 baskets/hour (3120 dishes/hour). The work height and the counterbalanced door facilitate loading while the double walls improve thermal-acoustic insulation. The rounded moulded tank with integral filters ensures maximum hygiene and perfect draining.

The dishwashers of the ELITECH line ensure maximum performance thanks to the standard Acquatech System which, through an atmospheric boiler and rinse pump, maintains constant temperature and pressure and optimum water consumption. Elitech ensures a sanitising rinse cycle and proves to be the perfect choice for canteens, nursing homes, pastry shops, bakers and butchers where compliance with HACCP rules is essential. For anyone seeking perfectly sparkling glasses, it is possible to connect a Reverse Osmosis System which purifies water and reduces detergent and rinse-aid consumption, ensuring excellent results and perfect glasses without the need for hand drying. The innovative UNIKO tempered glass touch screen display makes any operation simple and intuitive, from the choice of the most suitable wash cycle to its progress control, as well as constantly monitor the status of the dishwasher with ease. The large variety of wash cycles makes the dishwasher customisable according to your needs. Constant self-diagnosis allows you to minimise machine downtime, promptly warning the technician through the Wi-Fi IKLOUD control system that offers the possibility of remotely changing the dishwasher parameters and resolving the situation in real-time.

The electronic control allows you to manage various parameters to give you an absolute customisation level and the continuous self-diagnosis allows you to minimise machine downtime, suggesting some operations that need to be verified. The self-cleaning cycle at the end of the day cleans the wash tank and empties the hot water from the boiler, preventing limestone from building up inside. The standard double peristaltic electric rinse-aid and detergent dispenser ensures the best result from each wash cycle with great savings thanks to the precise dosage managed by the electronic card; whereas, the moulded washing and rinsing arms ensure great reliability and durability. The Thermo-stop function checks that washing and rinsing begin only when the desired temperature is reached. The bodywork is made entirely of AISI 304 steel and has been designed with all of the components in the front for easy technical assistance. Sturdy and reliable dishwashers to best deal with every moment of your day.

FHI C ∈ ⊕

♦WRAS









DISHWASHERS FEATURES	ELITECH RANGE EL991E
Dimensions - (mm) L - P - H	1440X860X2020/2300h
n° baskets/hour - (+55°C)	Max 30
Height pot max	830mm
LT bread basket	601
Trays	GN1/1 - 60x40 GN2/1 - 60x80
Tank heating element - Tank capacity	8,1kW - 100lt
Boiler heating element - Boiler capacity	8,1kW - 20,8lt
Washing pump	2,0kW - 2,7Hp x2
Total power input / Current	12,1kW / 32A
Standard input voltage	400V3N - 50Hz
Recommended inlet water temperature	+55°C
Water hardness	7°f - 10°f
Water consumption per cycle (inlet suggested pressure 2 BAR)	4,0
Adjustable detergent and rinse-aid dispenser	STANDARD
Acquatech system rinse	STANDARD
STANDARD EQUIPMENT	
8 division cutlery insert	2
Integral tank filter	STANDARD
Inox basket dim.600x670x100mm	2
Basket for trays with 5 compartments	2
OPTIONAL	
UNIKO touch display with IKLOUD Wi-Fi control	-
Built-in drain pump 190W with Ecoclean	•
Boiler heating element 9kW	•
Boiler heating element 9kW	•
"SOFT Door" Opening/Closing System	-
Optional Installabile, Optional not installable	

EL991E







